



Call our Expert Sales Team for more information.

First Fence Ltd | Kiln Way, Woodville, South Derbyshire, DE11 8EA
01283 512 111 | www.firstfence.co.uk | sales@firstfence.co.uk



Uncompromising Structural Support, Unrivalled Build Quality!

Our comprehensive range of Steel Lintels is a robust and dependable load-bearing solution for any scale of construction project. Engineered from high-quality, pre-galvanised mild steel, these lintels deliver exceptional corrosion and weather resistance, providing critical, long-lasting stability where your masonry needs it most. They act as a reliable foundation while strictly satisfying the rigorous thermal building regulations across England, Wales, Northern Ireland, and Scotland, ensuring your structure is supported without compromising on energy efficiency or safety.

This specification covers our complete Steel Lintel range, available in a variety of weight-loading capabilities to suit everything from standard lighter jobs to extra heavy-duty configurations for demanding builds. Supplied in an array of profiles—including Standard & HD Box, Wide Inner and Outer Leaf, Cavity Wall & Eaves, and Solid Wall formats—and rigorously tested to all relevant BS EN Standards, these lintels deliver a flawless, secure fit that ensures the long-term safety, compliance, and structural integrity of your project.

Key Features

- ✓ **Galvanised Construction**
(Made from pre-galvanised steel delivering resistance to corrosion and weathering)
- ✓ **Versatile Load-Bearing Capabilities**
(Available in a range of weight capacities for lighter jobs and demanding projects)
- ✓ **Profile Selection**
(Standard & HD Box Lintels, Solid Wall Lintels, Cavity Wall & Eaves and more)
- ✓ **Regulatory & Thermal Compliance**
(Meets relevant BS EN standards & thermal requirements of building regulations)
- ✓ **Rapid Availability**
(Backed by our quick and easy delivery service)

Suitable For

- ✓ Residential Window & Door Openings
- ✓ Commercial & Industrial Builds
- ✓ Property Extensions & Eaves Construction
- ✓ Structural Refurbishments
- ✓ Thermally Compliant Eco-Developments



Our steel lintels are manufactured from corrosion-resistant pre-galvanised mild steel, fully compliant with UK-wide thermal building regulations (Part L, Part F, and Section 6)

How to Choose the Right Steel Lintel:

- What is the wall construction? Is it a cavity wall? A solid wall, or timber frame?
- What is the required load capacity? Is it just supporting a few courses of brick, or is it carrying roof trusses and concrete floors?
- What is the opening size? Remember, a lintel must be longer than the opening. You must add a minimum 150mm bearing to each end.
- Are there specific thermal requirements? Does the lintel need integrated insulation to meet UK building regulations for eco-developments?

CAVITY WALL LINTELS

Best For: Standard UK cavity wall constructions.

When to Use: To bridge openings like windows or doors in traditional cavity walls. They span both the inner and outer masonry leaves to distribute weight evenly and include integrated insulation to prevent cold bridging and meet thermal regulations. Available in standard or heavy-duty.

WIDE INNER LEAF & WIDE OUTER LEAF LINTELS

Best For: Cavity walls with uneven or oversized stonework.
When to Use: When masonry exceeds the standard 100mm thickness. Specify a Wide Inner Leaf (WIL) for internal block work measuring 125mm–150mm to support heavier internal loads, or a Wide Outer Leaf (WOL) for thicker exterior façades like decorative stone.

SOLID WALL LINTELS

Best For: Single-skin walls and internal partitions with no cavity.
When to Use: Essential for solid brick or block walls (typically 200mm–215mm thick). These are the definitive solution for internal structural alterations—such as knocking through masonry for open-plan layouts—or for retrofitting older period properties built without cavities.

BOX LINTELS

Best For: Extreme heavy-duty load bearing and extra-wide structural spans.
When to Use: Specify these heavy lifters for the most demanding structural requirements, such as carrying concrete floor slabs, heavy roof trusses, or spanning wide openings like bi-fold doors. Their flat profile also makes them highly versatile for internal walls, as they accept plaster directly.

CAVITY WALL EAVES LINTELS

Best For: Window openings directly beneath the roof line.
When to Use: At the eaves level, where there is no masonry load on the outer wall. This lintel is precisely profiled to carry the full weight of the roof trusses on the inner leaf, while its shortened outer flange allows for a neat, seamless soffit finish.



Call our Expert Sales Team for more information.

BOX LINTELS	MATERIAL	HEIGHT	LENGTH	THICKNESS	WIDTH	TOTAL UDL kN
BOX/K-100 - Solid Wall Standard Load Bearing Box Lintel	Pre-Galvanised Steel	75mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm	1.6mm	100mm	15 (750-1500mm)
BOX/K-200 Standard Load Bearing Box Lintel	Pre-Galvanised Steel	150mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm	1.6mm (750mm - 1500mm) 2.0mm (1650mm - 2700mm)	215mm	15 (750 - 1500mm) 30 (1650 - 2100mm) 25 (2250 - 2400mm) 20 (2550 - 2700mm)
HDBOX/K-200 High Heavy Duty Load Bearing Box Lintel	Pre-Galvanised Steel	150mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm	2.5mm	215mm	30 (750 - 1200mm) 35 (1350 - 1800mm)
HDBOX/K-150 Solid Wall Heavy Duty Load Bearing Box Lintel	Pre-Galvanised Steel	150mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm	2.5mm	150mm	50 (750 - 1200mm) 45 (1350 - 1800mm)
HDBOX/K-100 Solid Wall Heavy Duty Load Bearing Box Lintel	Pre-Galvanised Steel	150mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm	2.5mm	100mm	50 (750 - 1200mm) 45 (1350 - 1800mm)
BOX/K-150 Solid Wall Standard Load Bearing Box Lintel	Pre-Galvanised Steel	150mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm	1.6mm (750mm - 1500mm) 2.0mm (1650mm - 2700mm)	150mm	15 (750 - 1500mm) 30 (1650 - 2100mm) 25 (2250 - 2400mm) 20 (2550 - 2700mm)
BOX/K-150 Solid Wall Standard Load Bearing Box Lintel	Pre-Galvanised Steel	215mm	2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm, 3750mm, 3900mm, 4050mm, 4200mm, 4350mm, 4500mm, 4650mm, 4800mm	2.5mm	150mm	35 (2850 - 3600mm) 30 (3750 - 4200mm) 25 (4350 - 4800mm)
BOX/K-200 Standard Load Bearing Box Lintel	Pre-Galvanised Steel	215mm	2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm, 3750mm, 3900mm, 4050mm, 4200mm, 4350mm, 4500mm, 4650mm, 4800mm	2.5mm	215mm	30 (2850 - 3600mm) 25 (3750 - 4200mm) 20 (4350 - 4800mm)
HDBOX/K-200 Heavy Duty Load Bearing Box Lintel	Pre-Galvanised Steel	215mm	1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm	2.5mm	215mm	45 (1950 - 2400mm) 40 (2550 - 2700mm)
HDBOX/K-150 Solid Wall Heavy Duty Load Bearing Box Lintel	Pre-Galvanised Steel	215mm	1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm	2.5mm	150mm	50 (1950 - 2400mm) 40 (2550 - 2700mm)
HDBOX/K-100 Solid Wall Heavy Duty Load Bearing Box Lintel	Pre-Galvanised Steel	215mm	1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm	2.5mm	100mm	50 (1950 - 2400mm) 40 (2550 - 2700mm)



Call our Expert Sales Team for more information.

WIDE INNER LEAF	MATERIAL	HEIGHT	LENGTH	LEAF WIDTH	THICKNESS	TOTAL UDL kN 3:1	TOTAL UDL kN 19:1
CFS/K-150 WIL Extra Heavy Duty Load Cavity Wall Lintel (150-165 Cavity)	Pre-Galvanised Steel	229mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm, 3750mm, 3900mm, 4050mm, 4200mm, 4350mm, 4500mm, 4650mm, 4800mm	Inner Leaf = 125mm Outer Leaf = 95mm	2.9mm (750 - 3000mm) 3.2mm (3150 - 4000mm)		70 (750 - 1500) 60 (1650 - 2100) 50 (2250 - 3000) 45 (3150 - 4000) 40 (4200 - 4800)
CFS/K-110 WIL Extra Heavy Duty Load Cavity Wall Lintel (110-125 Cavity)	Pre-Galvanised Steel	229mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm, 3750mm, 3900mm, 4050mm, 4200mm, 4350mm, 4500mm, 4650mm, 4800mm	Inner Leaf = 125mm Outer Leaf = 95mm	2.9mm (750 - 3000mm) 3.2mm (3150 - 4000mm)		70 (750 - 1500) 60 (1650 - 2100) 50 (2250 - 3000) 45 (3150 - 4000) 40 (4200 - 4800)
HD/K-110 WIL Heavy Duty Load Cavity Wall Lintel (110-125 Cavity)	Pre-Galvanised Steel	131mm (750-1350) 148mm (1500-1800) 195mm (1950-2700)	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm	Inner Leaf = 125mm Outer Leaf = 95mm	2.9mm (750 - 2100mm) 3.2mm (2250 - 2700mm)		17 (750 - 1350) 25 (1500 - 2100) 32 (2250 - 2700)
S/K-150 WIL Standard Load Cavity Wall Lintel (150-165 Cavity)	Pre-Galvanised Steel	88mm (750-1200) 115mm (1350-1800) 168mm (1950-3600)	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm	Inner Leaf = 125mm Outer Leaf = 95mm	2.0mm (750 - 1800mm) 2.5mm (1950 - 2100mm) 2.9mm (2250 - 3000mm) 3.2mm (3150 - 3600mm)	13 (750 - 1200) 17 (1350 - 1800) 23 (1950 - 2100) 24 (2250 - 3600)	11 (750 - 1200) 14 (1350 - 1800) 18 (1950 - 3000) 17 (3150 - 3600)
S/K-110 WIL Standard Load Cavity Wall Lintel (110-125 Cavity)	Pre-Galvanised Steel	95mm (750-1200) 107mm (1350-1800) 142mm (1950-2100) 185mm (2250-3600)	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm	Inner Leaf = 125mm Outer Leaf = 95mm	2.0mm (750 - 1800mm) 2.5mm (1950 - 2100mm) 2.9mm (2250 - 3000mm) 3.2mm (3150 - 3600mm)	13 (750 - 1200) 17 (1350 - 1800) 23 (1950 - 2100) 24 (2250 - 3600)	11 (750 - 1200) 14 (1350 - 1800) 18 (1950 - 3000) 17 (3150 - 3600)

WIDE OUTER LEAF	MATERIAL	HEIGHT	LENGTH	LEAF WIDTH	THICKNESS	TOTAL UDL kN 3:1	TOTAL UDL kN 19:1
S/K-150 WOL Standard Load Cavity Wall Lintel (150-165 Cavity)	Pre-Galvanised Steel	88mm (750-1350) 115mm (1500-1650) 168mm (1800-3600)	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm	Inner Leaf = 100mm Outer Leaf = 120mm	2.5mm (750 - 1350mm) 2.9mm (2250 - 2700mm) 3.2mm (2850 - 3600mm)	14 (750 - 1350) 15 (1500 - 1650) 23 (1800 - 2100) 30 (2250 - 2700) 32 (2850 - 3000) 30 (3150 - 3600)	11 (750 - 1350) 13 (1500 - 1650) 18 (1800 - 2100) 22 (2250 - 2700) 30 (2850 - 3000) 26 (3150 - 3600)
S/K-110 WOL Standard Load Cavity Wall Lintel (110-125 Cavity)	Pre-Galvanised Steel	95mm (750-1350) 107mm (1500-1650) 142mm (1800-2100) 185mm (2250-3600)	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm	Inner Leaf = 100mm Outer Leaf = 120mm	2.5mm (750 - 2100mm) 2.9mm (2250 - 2700mm) 3.2mm (2850 - 3600mm)	14 (750 - 1350) 15 (1500 - 1650) 23 (1800 - 2100) 30 (2250 - 2700) 32 (2850 - 3000) 30 (3150 - 3600)	11 (750 - 1350) 13 (1500 - 1650) 18 (1800 - 2100) 22 (2250 - 2700) 30 (2850 - 3000) 26 (3150 - 3600)
S/K-90 WOL Standard Load Cavity Wall Lintel (90-105 Cavity)	Pre-Galvanised Steel	93mm (750-1350) 110mm (1500-1650) 162mm (1800-2100) 188mm (2250-3600)	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm	Inner Leaf = 100mm Outer Leaf = 120mm	2.5mm (750 - 2100mm) 2.9mm (2250 - 3000mm) 3.2mm (3150 - 3600mm)	14 (750 - 1350) 15 (1500 - 1650) 23 (1800 - 2100) 30 (2250 - 2700) 32 (2850 - 3000) 30 (3150 - 3600)	11 (750 - 1350) 13 (1500 - 1650) 18 (1800 - 2100) 22 (2250 - 2700) 30 (2850 - 3000) 26 (3150 - 3600)



Call our Expert Sales Team for more information.

CAVITY WALL & EAVES	MATERIAL	HEIGHT	LENGTH	LEAF WIDTH	THICKNESS	TOTAL UDL kN 3:1	TOTAL UDL kN 19:1
EL/K - 90 Cavity Wall Eaves Lintel (90-125 Cavity)	Pre-Galvanised Steel	106mm (750-1500) 144mm (1650-2100) 163mm (2250-2400) 164mm (2550-2700)	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm	Inner Leaf = 100mm Outer Leaf = 45mm	1.8mm (750 - 1500mm) 2.0mm (1650 - 2400mm) 2.5mm (2550 - 2700mm)		18 (750 - 1500) 20 (1650 - 2100) 22 (2250 - 2400) 25 (2550 - 2700)
T/K - 50 Standard Load Bearing Cavity Wall Lintel for Timber Frames (50-65 Cavity)	Pre-Galvanised Steel	110mm (750-1800) 135mm (1950-2400) 175mm (2550-3600) 250mm (3750-4800)	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm, 3750mm, 3900mm, 4050mm, 4200mm, 4350mm, 4500mm, 4650mm, 4800mm	Outer Leaf = 95mm	2.0mm (750 - 1200mm) 2.5mm (1350 - 2400mm) 2.8mm (2550 - 3600mm) 3.0mm (3750 - 4800mm)		4 (750 - 1200) 5 (1350 - 2400) 9 (2550 - 3600) 12 (3750 - 4800)
S/K - 150 Standard Load Bearing Cavity Wall Lintel (150-165 Cavity)	Pre-Galvanised Steel	100mm (750-1500) 118mm (1640-1800) 130mm (1950-2100) 148mm (2250-2700) 173mm (2850-4000) 199mm (4200-4800)	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm, 3750mm, 3900mm, 4050mm, 4200mm, 4350mm, 4500mm, 4650mm, 4800mm	Inner Leaf = 100mm Outer Leaf = 95mm	2.0mm (750 - 2100mm) 2.5mm (2250 - 2700mm) 2.9mm (2850 - 3000mm) 3.2mm (3150 - 4800mm)	16 (750 - 1500) 22 (1640 - 1800) 21 (1950 - 2100) 25 (2250 - 2700) 27 (2850 - 3000) 26 (3150 - 4000) 25 (4200 - 4800)	13 (750 - 1500) 18 (1640 - 1800) 17 (1950 - 2100) 20 (2250 - 2700) 22 (2850 - 3000) 19 (3150 - 4000) 20 (4200 - 4800)
S/K - 110 Standard Load Bearing Cavity Wall Lintel (110-125 Cavity)	Pre-Galvanised Steel	97mm (750-1500) 113mm (1650-1800) 125mm (1950-2100) 163mm (2250-2700) 193mm (2850-4050) 218mm (4200-4800)	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm, 3750mm, 3900mm, 4050mm, 4200mm, 4350mm, 4500mm, 4650mm, 4800mm	Inner Leaf = 100mm Outer Leaf = 95mm	2.0mm (750 - 2100mm) 2.5mm (2550 - 2700mm) 2.9mm (2850 - 3000mm) 3.2mm (3150 - 4800mm)	16 (750 - 1500) 22 (1640 - 1800) 21 (1950 - 2100) 25 (2250 - 2700) 27 (2850 - 3000) 26 (3150 - 4050) 25 (4200 - 4800)	13 (750 - 1500) 18 (1640 - 1800) 17 (1950 - 2100) 20 (2250 - 2700) 22 (2850 - 3000) 19 (3150 - 4050) 20 (4200 - 4800)
HD/K - 110 Heavy Duty Load Bearing Cavity Wall Lintel (110-125 Cavity)	Pre-Galvanised Steel	97mm (750-1500) 113mm (1650-1800) 125mm (1950-2100) 163mm (2250-2700) 193mm (2850-4050) 218mm (4200-4800)	900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm, 3750mm, 3900mm, 4050mm	Inner Leaf = 100mm Outer Leaf = 95mm	2.9mm (900 - 2100mm) 3.2mm (2550 - 4050mm)	30 (900 - 2100) 35 (2250 - 3000) 32 (3150 - 3600) 30 (3750 - 4050)	20 (900 - 1500) 22 (1650 - 2100) 30 (2250 - 3000) 28 (3150 - 3600) 26 (3750 - 4050)
HD/K - 150 Heavy Duty Load Bearing Cavity Wall Lintel (150-165 Cavity)	Pre-Galvanised Steel	125mm (750-1500) 160mm (1650-2100) 180mm (2250-3600) 200mm (3750-4050)	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm, 3750mm, 3900mm, 4050mm	Inner Leaf = 100mm Outer Leaf = 95mm	2.9mm (750 - 2100mm) 3.2mm (2250 - 4050mm)	30 (750 - 2100) 35 (2250 - 3000) 30 (3150 - 4050)	20 (750 - 1500) 22 (1650 - 2100) 30 (2250 - 3000) 25 (3150 - 3600) 26 (3750 - 4050)
CFS/K - 90 Extra Heavy Duty Load Bearing Cavity Wall Lintel (90-105 Cavity)	Pre-Galvanised Steel	229mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm, 3750mm, 3900mm, 4050mm, 4200mm, 4350mm, 4500mm, 4650mm, 4800mm	Inner Leaf = 100mm Outer Leaf = 95mm	2.5mm (750 - 2400mm) 3.0mm (2550 - 4800mm)		48 (750 - 2400) 50 (2550 - 3600) 38 (3750 - 4800)
CFS/K - 110 Extra Heavy Duty Load Bearing Cavity Wall Lintel (110-125 Cavity)	Pre-Galvanised Steel	229mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm, 3750mm, 3900mm, 4050mm, 4200mm, 4350mm, 4500mm, 4650mm, 4800mm	Inner Leaf = 100mm Outer Leaf = 95mm	2.5mm (750 - 2400mm) 3.0mm (2550 - 4800mm)		48 (750 - 2400) 50 (2550 - 3600) 38 (3750 - 4800)
CFS/K - 150 Extra Heavy Duty Load Bearing Cavity Wall Lintel (150-165 Cavity)	Pre-Galvanised Steel	229mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm, 3750mm, 3900mm, 4050mm, 4200mm, 4350mm, 4500mm, 4650mm, 4800mm	Inner Leaf = 100mm Outer Leaf = 95mm	2.5mm (750 - 2400mm) 3.0mm (2550 - 4800mm)		48 (750 - 2400) 50 (2550 - 3600) 38 (3750 - 4800)



SOLID WALL LINTELS	MATERIAL	HEIGHT	LENGTH	LEAF WIDTH	THICKNESS	TOTAL UDL kN
SW/K Standard Load Lintel for Solid Walls	Pre-Galvanised Steel	55mm (750-1800) 100mm (1950-2700)	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm	195mm	2.5mm (750 - 1500mm) 3.0mm (1650 - 2700mm)	6 (750 - 1800) 10 (1950 - 2700)
SL/K Heavy Duty Load Single Leaf Lintel for Solid Walls	Pre-Galvanised Steel	225mm	1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm, 2580mm, 3000mm	95mm	2.5mm (1950 - 2400mm) 3.0mm (2550 - 3000mm)	20 (1950 - 2400) 22 (2550 - 3000)
SL/K Heavy Duty Load Single Leaf Lintel for Solid Walls	Pre-Galvanised Steel	150mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm	95mm	2.5mm (750 - 1800mm)	16 (750 - 1800)
BOX/K-75 Solid Wall Standard Load Bearing Box Lintel	Pre-Galvanised Steel	75mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm,	95mm	1.6mm (750 - 1650mm) 2.0mm (1800)	15 (750 - 1650) 10 (1800)
BOX/K-100 Solid Wall Standard Load Bearing Box Lintel	Pre-Galvanised Steel	75mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm	100mm	1.6mm (750 - 1500mm)	15 (750 - 1500)
HDBOX/K-100 Solid Wall Heavy Duty Load Bearing Box Lintel	Pre-Galvanised Steel	150mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm	100mm	2.5mm (750 - 1800mm)	50 (750 - 1200) 45 (1350 - 1800)
BOX/K-100 Solid Wall Standard Load Bearing Box Lintel	Pre-Galvanised Steel	150mm	1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm	100mm	2.0mm (1650 - 2700mm)	30 (1650 - 2100) 25 (2550 - 2400) 20 (2550 - 2700)
BOX/K-150 Solid Wall Standard Load Bearing Box Lintel	Pre-Galvanised Steel	150mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm, 1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm	150mm	1.6mm (750 - 1500mm) 2.0mm (1650 - 2700mm)	15 (750 - 1500) 30 (1650 - 2100) 25 (2250 - 2400) 20 (2550 - 2700)
HDBOX/K-150 Solid Wall Heavy Duty Load Bearing Box Lintel	Pre-Galvanised Steel	150mm	750mm, 900mm, 1050mm, 1200mm, 1350mm, 1500mm, 1650mm, 1800mm	150mm	2.5mm (750 - 1800mm)	50 (750 - 1200) 45 (1350 - 1800)
BOX/K-150 Solid Wall Standard Load Bearing Box Lintel	Pre-Galvanised Steel	215mm	2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm, 3750mm, 3900mm, 4050mm, 4200mm, 4350mm, 4500mm, 4650mm, 4800mm	150mm	2.5mm (2850 - 4800mm)	35 (2850 - 3600) 30 (3750 - 4200) 25 (4350 - 4800)
HDBOX/K-150 Solid Wall Heavy Duty Load Bearing Box Lintel	Pre-Galvanised Steel	215mm	1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm	150mm	2.5mm (1950 - 2700mm)	50 (1950 - 2400) 40 (2550 - 2700)
HDBOX/K-100 Solid Wall Heavy Duty Load Bearing Box Lintel	Pre-Galvanised Steel	215mm	1950mm, 2100mm, 2250mm, 2400mm, 2550mm, 2700mm	100mm	2.5mm (1950 - 2700mm)	50 (1950 - 2400) 40 (2550 - 2700)
BOX/K-100 Solid Wall Standard Load Bearing Box Lintel	Pre-Galvanised Steel	215mm	2850mm, 3000mm, 3150mm, 3300mm, 3450mm, 3600mm, 3750mm, 3900mm, 4050mm, 4200mm, 4350mm, 4500mm, 4650mm, 4800mm	100mm	2.5mm (2850 - 4800mm)	35 (2850 - 3600) 25 (3750 - 4200) 20 (4350 - 4800)

