


FF9500 Auto Bi-Folding Gate	2.0 Metre Width - Single Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	2.5 Metre Width - Single Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	3.0 Metre Width - Single Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	3.5 Metre Width - Single Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	4.0 Metre Width - Single Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	4.5 Metre Width - Single Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	5.0 Metre Width - Single Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	3.0 Metre Width - Double Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	3.5 Metre Width - Double Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	4.0 Metre Width - Double Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	4.5 Metre Width - Double Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	5.0 Metre Width - Double Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	5.5 Metre Width - Double Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	6.0 Metre Width - Double Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	6.5 Metre Width - Double Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	7.0 Metre Width - Double Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	7.5 Metre Width - Double Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	8.0 Metre Width - Double Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	8.5 Metre Width - Double Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	9.0 Metre Width - Double Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	9.5 Metre Width - Double Leaf (Up To 2.4m High)
FF9500 Auto Bi-Folding Gate	10.0 Metre Width - Double Leaf (Up To 2.4m High)

Specification	CE Approved BS/EN 12453
Maximum Span	10 Metres Drive-Through
Maximum Height	2.4 Metres
Finish	Powder Coated (Galvanised Optional)
Power Requirements	Single Phase 240V, 50Hz, 10 Amps
Drive Motor	3 Phase Motor & Wormed Gearbox
Duty Cycles	100% Continuous Duty Cycle Rating
Operation Time	4 - 10 Seconds (Dependant on Version)



FF9500 Product Features



The FF9500 Bi-Folding Trackless Speed Gates are the ideal solutions where speed of opening and closing is essential or where space is at a premium.

The FF9500 bi-folding trackless speed gates typically open at more than twice the speed of a traditional swinging gates of the same size which ensures a fast throughput of traffic whilst maintaining security of the site.

The FF9500 utilises a driven integrated frequency converter, single phase power, supplying a 3 phase motor, worm and wheel gearbox with a direct-drive shaft connected to the gate leaf, which ensures a smooth and positive movement. FF9500 speed gates are rated for 100% duty cycle i.e. continuous operation.

A wide range of alternative infills are available to suit customers requirements and to match adjoining fencing design. Also available are spiked tops, warning lights and sirens if required.

The gates are supplied with a programmable logic control board which is mounted in the main pillar of the gate.

The FF9500 Bi-Folding Gates comply with BS/EN 12453 (ALL automated gates must comply with the current legislation). We fit as standard a number of safety devices, including dual height photocells and category 2/3 safety edges.

FF9500 Speed Gate Optional Extras

- Razor Wire Extensions
- Electric Fence
- Anti-Climb Spikes
- Traffic Lights
- Warning Siren
- Timber Infills
- Louvre Infills

Options for Access Control

- Keypad
- Proximity Cards
- Voice/Video Intercom Access
- Token Acceptors
- Remote Control Fobs
- Key Switches
- Loop Detectors
- Photocells