SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
UK REACH Regulations (SI 2019/758 as amended)

Revision date 27/06/2023 **Revision Number** 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Code(s) 3559

Product Name 3559 - First Fence Limited - First Fence RAL5010 Blue Spray 400ml Aerosols SPRAY-PA-5010

Pure substance/mixture Mixture

Contains Acetone, Xylene, Hydrocarbons, C9, aromatics

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Paint

1.3. Details of the supplier of the safety data sheet

Manufacturer

Specialised Chemicals Ltd
Tollemache Road South
Spittlegate Level Industrial Estate
Grantham
Lincolnshire
NG317UH
Tel: +44 (0) 1476 567615

For further information, please contact;

Emergency Telephone +44(0)1476 567615 (Mon to Fri 09:00 - 17:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity — single exposure	Category 3 - (H335, H336)
Category 3 Respiratory irritation, Narcotic effects	
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Chronic aquatic toxicity	Category 3 - (H412)
Aerosols	Category 1 - (H222, H229)

2.2. Label elements

Contains Acetone, Xylene, Hydrocarbons, C9, aromatics



Signal word
Danger

Hazard statements
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H373 - May cause damage to organs through prolonged or repeated exposure
H412 - Harmful to aquatic life with long lasting effects
H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
EUH066 - Repeated exposure may cause skin dryness or cracking
For professional users only

Precautionary statements
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P261 - Avoid breathing vapours/spray
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P312 - Call a POISON CENTER or doctor if you feel unwell
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Additional information
This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

Harmful to aquatic life.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	EC No (EU Index No)	UK REACH registration number	Classification according to GB CLP (SI 2020/1567 as amended)	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)
PETROLEUM GASES, LIQUEFIED	30-60%	() 270-704-2	-	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-

<0.1% 1,3-BUTADIENE 68476-85-7							
Acetone 67-64-1	10-30%	() 200-662-2	-	(EUH066) Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 (H336)	-	-	-
Xylene 1330-20-7	10-30%	() 215-535-7	-	Flam. Liq. 3 (H226) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Asp. Tox. 1 (H304) STOT RE 2 (H373) Eye Irrit. 2 (H319) STOT SE 3 (H335) Aquatic Chronic 3 (H412)	-	-	-
Hydrocarbons, C9, aromatics 128601-23-0	1-5%	918-668-5	-	Flam. Liq. 3 (H226) Asp.Tox. 1 (H304) STOT SE 3 (H335 & H336) Aquatic Chronic 2 (H411)	-	-	-
Ethylbenzene 100-41-4	1-5%	(601-023-00-4) 202-849-4	-	Flam. Liq. 2 (H225) Acute Tox. 4 (H332) STOT RE 2 (H373) Asp. Tox. 1 (H304)	-	-	-
Trizinc bis(orthophosphate) 7779-90-0	<1%	(030-011-00-6) 231-944-3	-	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	-	-	-
Methyl Proxitol Acetate 108-65-6	<1%	(607-195-00-7) 203-603-9	-	Flam. Liq. 3 (H226) STOT SE 3 (H336)	-	-	-
n-butyl acetate 123-86-4	<1%	(607-025-00-1) 204-658-1	-	(EUH066) Flam. Liq. 3 (H226) STOT SE 3 (H336)	-	-	-
Hydrocarbons, C9, aromatics 64742-95-6	<1%	(649-356-00-4) 265-199-0	-	Flam. Liq. 3 (H226) Asp. Tox. 1 (H304) STOT SE 3 (H335 & H336) Aquatic Chronic 2 (H411)	-	-	-
Zinc oxide 1314-13-2	<1%	(030-013-00-7) 215-222-5	-	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	-	-	-

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >= 0.1% (UK REACH Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur.

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals.

7.3. Specific end use(s)

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	United Kingdom
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE 68476-85-7	TWA: 1000 ppm TWA: 1750 mg/m³ STEL: 1250 ppm STEL: 2180 mg/m³
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m³ STEL: 1500 ppm STEL: 3620 mg/m³
Xylene 1330-20-7	TWA: 50 ppm TWA: 220 mg/m³ STEL: 100 ppm STEL: 441 mg/m³ Sk*
Ethylbenzene 100-41-4	TWA: 100 ppm TWA: 441 mg/m³ STEL: 125 ppm STEL: 552 mg/m³ Sk*
Methyl Proxitol Acetate 108-65-6	TWA: 50 ppm TWA: 274 mg/m³ STEL: 100 ppm STEL: 548 mg/m³ Sk*
n-butyl acetate 123-86-4	TWA: 150 ppm TWA: 724 mg/m³ STEL: 200 ppm STEL: 966 mg/m³

Biological occupational exposure limits

Chemical name	United Kingdom
Xylene 1330-20-7	650 mmol/mol creatinine - urine (Methyl hippuric acid) - post shift

Derived No Effect Level (DNEL) - Workers No information available

Chemical name	Oral	Dermal	Inhalation
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE 68476-85-7		23.4 mg/kg bw/day [4] [6]	
Acetone 67-64-1		186 mg/kg bw/day [4] [6]	1210 mg/m³ [4] [6] 2420 mg/m³ [5] [7]
Xylene 1330-20-7		212 mg/kg bw/day [4] [6]	221 mg/m³ [4] [6] 442 mg/m³ [4] [7] 221 mg/m³ [5] [6] 442 mg/m³ [5] [7]
Ethylbenzene 100-41-4		180 mg/kg bw/day [4] [6]	77 mg/m³ [4] [6] 293 mg/m³ [5] [7]
Trizinc bis(orthophosphate) 7779-90-0		83 mg/kg bw/day [4] [6]	5 mg/m³ [4] [6]

Chemical name	Oral	Dermal	Inhalation
Methyl Proxitol Acetate 108-65-6		796 mg/kg bw/day [4] [6]	275 mg/m³ [4] [6] 550 mg/m³ [5] [7]
Hydrocarbons, C9, aromatics 64742-95-6			1286.4 mg/m³ [4] [7] 837.5 mg/m³ [5] [6] 1066.67 mg/m³ [5] [7]
Zinc oxide 1314-13-2		83 mg/kg bw/day [4] [6]	5 mg/m³ [4] [6] 0.5 mg/m³ [5] [6]

Derived No Effect Level (DNEL) - General Public No information available.

Chemical name	Oral	Dermal	Inhalation
Acetone 67-64-1	62 mg/kg bw/day [4] [6]		200 mg/m³ [4] [6]
Xylene 1330-20-7	12.5 mg/kg bw/day [4] [6]		65.3 mg/m³ [4] [6] 260 mg/m³ [4] [7] 65.3 mg/m³ [5] [6] 260 mg/m³ [5] [7]
Ethylbenzene 100-41-4	1.6 mg/kg bw/day [4] [6]		15 mg/m³ [4] [6]
Trizinc bis(orthophosphate) 7779-90-0	0.83 mg/kg bw/day [4] [6]		2.5 mg/m³ [4] [6]
Methyl Proxitol Acetate 108-65-6	36 mg/kg bw/day [4] [6]		33 mg/m³ [4] [6] 33 mg/m³ [5] [6]
Hydrocarbons, C9, aromatics 64742-95-6			1152 mg/m³ [4] [7] 178.57 mg/m³ [5] [6] 640 mg/m³ [5] [7]
Zinc oxide 1314-13-2	0.83 mg/kg bw/day [4] [6]		2.5 mg/m³ [4] [6]

Predicted No Effect Concentration (PNEC) No information available.

Chemical name	Freshwater	Freshwater (intermittent release)	Marine water	Marine water (intermittent release)	Air
Acetone 67-64-1	10.6 mg/L	21 mg/L	1.06 mg/L		
Xylene 1330-20-7	0.327 mg/L	0.327 mg/L	0.327 mg/L		
Trizinc bis(orthophosphate) 7779-90-0	20.6 µg/L		6.1 µg/L		
Methyl Proxitol Acetate 108-65-6	0.635 mg/L	6.35 mg/L	0.0635 mg/L		
n-butyl acetate 123-86-4	0.18 mg/L	0.36 mg/L	0.018 mg/L		
Zinc oxide 1314-13-2	20.6 µg/L		6.1 µg/L		

Chemical name	Freshwater sediment	Marine sediment	Sewage treatment	Soil	Food chain
Acetone 67-64-1	30.4 mg/kg sediment dw	3.04 mg/kg sediment dw	100 mg/L	29.5 mg/kg soil dw	
Xylene	12.46 mg/kg	12.46 mg/kg	6.58 mg/L	2.31 mg/kg soil dw	

Chemical name	Freshwater sediment	Marine sediment	Sewage treatment	Soil	Food chain
1330-20-7	sediment dw	sediment dw			
Trizinc bis(orthophosphate) 7779-90-0	117.8 mg/kg sediment dw	56.5 mg/kg sediment dw	100 µg/L	35.6 mg/kg soil dw	
Methyl Proxitol Acetate 108-65-6	3.29 mg/kg sediment dw	0.329 mg/kg sediment dw	100 mg/L	0.29 mg/kg soil dw	
n-butyl acetate 123-86-4	0.981 mg/kg sediment dw	0.0981 mg/kg sediment dw	35.6 mg/L	0.0903 mg/kg soil dw	
Zinc oxide 1314-13-2	117.8 mg/kg sediment dw	56.5 mg/kg sediment dw	100 µg/L	35.6 mg/kg soil dw	

8.2. Exposure controls

Engineering controls No information available.

Personal protective equipment

Eye/face protection Tight sealing safety goggles. Safety glasses with side shields are recommended for medical or industrial exposures.

Hand protection Impervious gloves. Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Aerosol
Colour blue
Odour Solvent.

Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	-41 174	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	13.0	
Lower flammability or explosive limits	0.8	
Flash point	No data available	None known
Autoignition temperature	333	None known
Decomposition temperature		None known
pH	No data available	None known
pH (as aqueous solution)	No data available	None known

Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Water solubility	Insoluble in water	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	0.76	None known
Bulk density	No data available	
Liquid Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size		
Particle Size Distribution		
Explosive properties	No information available	
Oxidising properties	No information available	

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data
Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 9,362.00 mg/kg
ATEmix (dermal) 4,746.80 mg/kg
ATEmix (inhalation-dust/mist) 12.10 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m³ (Rat) 8 h
Xylene	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
Ethylbenzene	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
Trizinc bis(orthophosphate)	> 5000 mg/kg (Rat)	-	-
Methyl Proxitol Acetate	= 8532 mg/kg (Rat)	> 5 g/kg (Rabbit)	= 16000 mg/m³ (Rat) 6 h
n-butyl acetate	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 0.74 mg/L (Rat) 4 h
Hydrocarbons, C9, aromatics	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Zinc oxide	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 5700 mg/m³ (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation. May cause skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

Reproductive toxicity No information available.

STOT - single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Unknown aquatic toxicity Contains 0 % of components with unknown hazards to the aquatic environment.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Acetone	-	LC50: 4.74 - 6.33mL/L (96h, Oncorhynchus mykiss) LC50: 6210 - 8120mg/L (96h, Pimephales promelas) LC50: =8300mg/L (96h, Lepomis macrochirus)	-	EC50: 10294 - 17704mg/L (48h, Daphnia magna) EC50: 12600 - 12700mg/L (48h, Daphnia magna)
Xylene	EC50: =11mg/L (72h, Pseudokirchneriella subcapitata)	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata)	-	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)
Ethylbenzene	EC50: =4.6mg/L (72h, Pseudokirchneriella	LC50: 11.0 - 18.0mg/L (96h, Oncorhynchus	-	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)

	subcapitata) EC50: >438mg/L (96h, Pseudokirchneriella subcapitata) EC50: 2.6 - 11.3mg/L (72h, Pseudokirchneriella subcapitata) EC50: 1.7 - 7.6mg/L (96h, Pseudokirchneriella subcapitata)	mykiss) LC50: =4.2mg/L (96h, Oncorhynchus mykiss) LC50: 7.55 - 11mg/L (96h, Pimephales promelas) LC50: =32mg/L (96h, Lepomis macrochirus) LC50: 9.1 - 15.6mg/L (96h, Pimephales promelas) LC50: =9.6mg/L (96h, Poecilia reticulata)		
Methyl Proxitol Acetate	-	LC50: =161mg/L (96h, Pimephales promelas)	-	EC50: >500mg/L (48h, Daphnia magna)
n-butyl acetate	EC50: =674.7mg/L (72h, Desmodesmus subspicatus)	LC50: =100mg/L (96h, Lepomis macrochirus) LC50: 17 - 19mg/L (96h, Pimephales promelas)	-	-
Hydrocarbons, C9, aromatics	-	LC50: =9.22mg/L (96h, Oncorhynchus mykiss)	-	EC50: =6.14mg/L (48h, Daphnia magna)
Zinc oxide	-	LC50: =1.55mg/L (96h, Danio rerio)	-	-

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE	<=2.8
Acetone	-0.24
Xylene	2.77 - 3.15
Ethylbenzene	3.6
Methyl Proxitol Acetate	1.2
n-butyl acetate	1.81 2.3

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

Chemical name	PBT and vPvB assessment
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE	The substance is not PBT / vPvB
Acetone	The substance is not PBT / vPvB
Xylene	The substance is not PBT / vPvB
Hydrocarbons, C9, aromatics	The substance is not PBT / vPvB
Ethylbenzene	The substance is not PBT / vPvB
Trizinc bis(orthophosphate)	PBT assessment does not apply
Methyl Proxitol Acetate	The substance is not PBT / vPvB
n-butyl acetate	The substance is not PBT / vPvB
Hydrocarbons, C9, aromatics	The substance is not PBT / vPvB
Zinc oxide	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

SECTION 14: Transport information

IATA

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols, flammable
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	A145, A167, A802
ERG Code	10L

IMDG

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1, Marine pollutant
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	63,190, 277, 327, 344, 381, 959
EmS-No	F-D, S-U
14.7 Maritime transport in bulk according to IMO instruments	

RID

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1, Environmentally Hazardous
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	190, 327, 344, 625
Classification code	5F

ADR

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1, (D), Environmentally Hazardous

14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	190, 327, 344, 625
Classification code	5F
Tunnel restriction code	(D)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Authorisations and/or restrictions on use:
This product does not contain substances subject to authorisation (UK REACH - Annex XIV). This product does not contain substances subject to restriction (UK REACH - Annex XVII).

Persistent Organic Pollutants
Not applicable

Export Notification requirements
Not applicable

Dangerous substance category per COMAH Regulations 2015 (as amended)
P3a - FLAMMABLE AEROSOLS
P3b - FLAMMABLE AEROSOLS

Named dangerous substances per COMAH Regulations 2015 (as amended)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE - 68476-85-7	50	200
Hydrocarbons, C9, aromatics - 64742-95-6	-	25000

The Ozone-Depleting Substances Regulations 2015
Not applicable

The Biocidal Products Regulations 2001 (as amended)
Not applicable

The Water Environment (Water Framework Directive) (England and Wales) Regulations 2017 (as amended)
Not applicable

Poisons Act 1972 (Explosive Precursors) Regulations (as Amended)

Chemical name	Poisons and Explosive Precursors
Acetone	Explosive precursor, Reportable

International Inventories

TSCA	See inventories below
DSL/NDSL	See inventories below
EINECS/ELINCS	See inventories below
ENCS	See inventories below
IECSC	See inventories below
KECL	See inventories below
PICCS	See inventories below
AIIC	See inventories below
NZIoC	See inventories below

Legend:
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AIIC - Australian Inventory of Industrial Chemicals
NZIoC - New Zealand Inventory of Chemicals

15.2. Chemical safety assessment

Chemical Safety Report No information available

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3
EUH066 - Repeated exposure may cause skin dryness or cracking
H220 - Extremely flammable gas
H225 - Highly flammable liquid and vapour
H226 - Flammable liquid and vapour
H280 - Contains gas under pressure; may explode if heated
H304 - May be fatal if swallowed and enters airways
H312 - Harmful in contact with skin
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H373 - May cause damage to organs through prolonged or repeated exposure
H412 - Harmful to aquatic life with long lasting effects

Legend
SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitisers		

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method

Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method
Flammable aerosol	On basis of test data

Key literature references and sources for data used to compile the SDS
Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australian National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine’s PubMed database (NLM PUBMED)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Revision date 27/06/2023

This material safety data sheet complies with the requirements of UK REACH Regulations (SI 2019/758 as amended) Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

UK SDS version information - XGHS
UL release:
GHS Revision 7
2022 Q1

United Kingdom Full process, including GHS and Transportation Wizards

Specific target organ toxicity — single exposure	Category 3
Category 3 Target organ effects: Respiratory irritation, Narcotic effects.	
Specific target organ toxicity — repeated exposure	Category 2

Full text of H-Statements referred to under section 3: EUH066 - Repeated exposure may cause skin dryness or cracking H220 - Extremely flammable gas H225 - Highly flammable liquid and vapour H226 - Flammable liquid and vapour H280 - Contains gas under pressure; may explode if heated H304 - May be fatal if swallowed and enters airways H312 - Harmful in contact with skin H315 - Causes skin irritation H319 - Causes serious eye irritation H332 - Harmful if inhaled H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness H373 - May cause damage to organs through prolonged or repeated exposure H412 - Harmful to

aquatic life with long lasting effects

Chemical name	Classification according to GB CLP (SI 2020/1567 as amended)	Specific concentration limit (SCL)
PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE	Flam. Gas 1 (H220) Press. Gas (H280)	
Acetone	(EUH066) Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 (H336)	
Xylene	Flam. Liq. 3 (H226) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Asp. Tox. 1 (H304) STOT RE 2 (H373) Eye Irrit. 2 (H319) STOT SE 3 (H335) Aquatic Chronic 3 (H412)	
Hydrocarbons, C9, aromatics	Flam. Liq. 3 (H226) Asp.Tox. 1 (H304) STOT SE 3 (H335 & H336) Aquatic Chronic 2 (H411)	
Ethylbenzene	Flam. Liq. 2 (H225) Acute Tox. 4 (H332) STOT RE 2 (H373) Asp. Tox. 1 (H304)	
Trizinc bis(orthophosphate)	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	
Methyl Proxitol Acetate	Flam. Liq. 3 (H226) STOT SE 3 (H336)	
n-butyl acetate	(EUH066) Flam. Liq. 3 (H226) STOT SE 3 (H336)	
Hydrocarbons, C9, aromatics	Flam. Liq. 3 (H226) Asp. Tox. 1 (H304) STOT SE 3 (H335 & H336) Aquatic Chronic 2 (H411)	
Zinc oxide	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	