

## Stock Fencing- L10/120/15 (6") | 47"

L = LIGHT GRADE

10 = NUMBER OF LINE WIRES

120 = HEIGHT IN CM

15 = DISTANCE BETWEEN VERTICALS IN CM

## **Key Features**

- A universal 4ft high fence.
- Useful in construction of dog fences.
- Used in areas of low stock pressure as a

taller option to standard fencing.

- Manufactured to BS EN 10223-5
- Galvanised to BS EN 10244-2 class A
- Tension curve to protect the fence.
- Hinge Joint.



| 204mm |                              |  |
|-------|------------------------------|--|
| 180mm |                              |  |
| 152mm |                              |  |
| 140mm |                              |  |
| 131mm |                              |  |
| 114mm |                              |  |
| 102mm |                              |  |
| 83mm  |                              |  |
| 83mm  |                              |  |
|       | <del>&lt;&gt;</del><br>15 cm |  |

## **Specification**

| Line wires                      | 10                    |
|---------------------------------|-----------------------|
| Distance between vertical wires | 15cm                  |
| Height                          | 120cm                 |
| Top and bottom line wires       | 2.5mm - 695-850 N/mm2 |
| Intermediate line wires         | 2.0mm - 695-850 N/mm2 |
| Vertical wires                  | 2.0mm - 415-550 N/mm2 |
| Roll lengths available          | 50m                   |
| Weight of 50m roll              | 26kg                  |
|                                 |                       |