



Call our Expert Sales Team for more information.

First Fence Ltd | Kiln Way, Woodville, South Derbyshire, DE11 8EA
01283 512 111 | www.firstfence.co.uk | sales@firstfence.co.uk



Support and Guidance for Smooth Operating Gates

Engineered to optimise stability and smooth operational performance, our range of adjustable guide rollers and plates provides a heavy-duty, reliable solution for residential, commercial, and industrial sliding or cantilever gate systems.

Manufactured with a protective white galvanised zinc finish, these components deliver high corrosion resistance and weatherproofing, ensuring maximum durability with minimal long-term maintenance.

Key Features

- ⊙ **High-Capacity Bottom Load Bearing**
(Gate's downward weight is transferred, eliminating pull on side posts)
- ⊙ **Integrated Precision Bearings**
(Deliver smooth, low-friction rotation)
- ⊙ **Versatile Mounting Plates**
(Equipped with pre-drilled brackets for easy bolting to steel posts or concrete pads)
- ⊙ **Grease Maintenance Point**
(External grease fitting for easy routine lubrication without dismantling)
- ⊙ **Heavy-Duty Galvanised Finish**
(Comes with a protective yellow zinc finish for resilience in harsh conditions)

Suitable For

- ⊙ Heavy Commercial & Industrial Gates
- ⊙ Automated Swing Gate Systems
- ⊙ Bi-Folding & Multi-Leaf Gate Systems
- ⊙ Pillar & Masonry Archway Installation
- ⊙ High-Traffic Security & Access Gates



Photos for illustration purposes only

Technical Specifications

Medium Adjustable Guide Plate 4RMR

Medium Adjustable Guide Plate (4-Roller).

Adjustable Width: Up to 90mm capacity to fit various gate frames.

Rollers: Includes 4x 40mm diameter rollers (CN40) for smooth operation.

Mounting & Finish: Weld-on post attachment with a protective white galvanised coating for superior corrosion resistance.



2 Guide Rollers and Plate to be Fixed to Wall 2RGZ

Mounting: Attaches to a wall or gate post.

Gate Compatibility: Suitable for flat-top gates only.

Adjustable Gap: Fits gate thicknesses from 37mm to 106mm.

Rollers Included: Comes with two 30mm diameter guide rollers (CN30).

Finish: Weather-resistant white galvanised coating.



Adjustable Roller Plate for Sliding Gates 2RGGZ

Mounting: Post-mounted (adjusts between 78mm – 112mm post width.)

Rollers: Includes 2x 40mm diameter guide rollers.

Compatibility: Works with 58/40 U-guide channel.

Interior Support: Fits on the inside of the gate to keep hardware invisible from the street.

Ideal For: Bow-top gates, spiked tops, or any installation requiring a clean, seamless appearance.

Finish: Weather-resistant galvanised coating.



Call our Expert Sales Team for more information.