

# **AntlerGuard® Deer Fencing**

Specification sheet SPC-ANT-001B

# **Key Features**

- - (Mesh can be directly attached to posts, minimal set up required)
- Choice of Post Finishes
- (Tanalised UC4 or creosoted finish to suit various needs and purposes)
- Cost Effective
  - (Low cost mesh rolls for demarcation or keeping animals safe)
- ⊘Galvanised to BS 10346
- (Galvanised finish compliant to latest standards)

  Strength & Resiliance
- (High-tensile square mesh, resistant to pressure from wind and animals)

## **Suitable For**

- ⊘ Fields
- **⊘**Crops
- ODeer keeping
- Scavenger protection
- ⊘Flat ground or inclines





## Visually unobstructive

Square mesh design allows for unobstructed view for keeping an eye on crops or animals, close up or from afar.



#### High-strength wire

High tensile wire in a square mesh pattern gives strength enough to stand against regular pressure from wind, animals and pedestrians.



### **Smaller spacing**

 $Antler Guard ^0 has a smaller mesh spacing, specifically designed so deer can't reach their mouths or hooves through, keeping them safe and secure.\\$ 



## Strong and secure

With a high tensile strength and fixed knot joints, this mesh offers enough protection to last throughout consistent use

# **Specifications**

Roll height 190cm

Roll length 100m per roll

Wire thicknesses LHT: 2.0mm

HT: 2.5mm

Tensile strength Horizontal: 1235-1390 N/mm2

Vertical: 695-850 N/mm2

Material Galvanised steel (BS 10346)

Finish Zinc coated for longevity

Roll weight LHT: 45kg

HT: 70.4kg

Post centers Intermediate strainer post every 3m (approx)

Knot type Fixed knot

Recommended Fixings Fencing Staples

J-Pins

Gripple Plus

S Call our Expert Sales Team for more information

First Fence Ltd | Kiln Way, Woodville, South Derbyshire, DE11 8EA 01283 512 111 | www.firstfence.co.uk | sales@firstfence.co.uk

Bristol | Canvey | Glasgow | Nottingham | Tipton













