

PastureGuard® Stock Fencing

Specification sheet SPC-PAS-001B

Key Features

- Easy Installation
 (Mesh can be directly attached to posts, minimal set up required)
- Choice of Post Finishes
 (Tanalised UC4 or creosoted finish to suit various needs and purposes)
- Cost Effective (Low cost mesh rolls for demarcation or keeping animals safe)
- Galvanised to BS 10346 (Galvanised finish compliant to latest standards)
- Strength & Resiliance (High-tensile square mesh, resistant to pressure from wind and animals)

Suitable For

- ⊘ Fields
- ⊘Crops
- ⊘Livestock
- Scavenger protection
- ○Flat Ground or Inclines





Visually unobstructive

Square mesh design allows for unobstructed view for keeping an eye on crops or animals, close up or from afar.



High-strength wire

High tensile wire in a square mesh pattern gives strength enough to stand against regular pressure from wind, animals and pedestrians.



Size variation

With a variety of heights, wire thicknesses, and mesh sizes, the PastureGuard® range is designed with versatility in mind.



Strong and secure

With a high tensile strength and strong joints, this mesh offers enough protection to last throughout consistent use

Specifications

Roll heights Light: 60cm, 80cm, or 120cm

Medium: 80cm, 90cm, 100cm, or 120cm

Heavy: 80cm

Roll length 50m per roll

Wire Thicknesses Light: 2.5mm/2.0mm

Medium: 3.0mm/2.5mm/2.0mm

Heavy: 4.0mm/3.0mm

Tensile strength Horizontal: 695 - 850 N/mm2

Vertical: 415 - 550 N/mm2

Material Galvanised steel (BS 10346)

Finish Zinc coated for longevity

Roll weight Ranging from 12.73kg to 48.06kg

Post Centers Intermediate strainer post every 3m (approx)

Knot type Hinge joint

Recommended Fixings Fencing Staples

J-Pins

Solution Call our Expert Sales Team for more information

First Fence Ltd | Kiln Way, Woodville, South Derbyshire, DE11 8EA 01283 512 111 | www.firstfence.co.uk | sales@firstfence.co.uk

Bristol | Canvey | Glasgow | Nottingham | Tipton













