

Key Features

- ⦿ **Easy Installation**
(Wire can be directly attached to posts, minimal set up required)
- ⦿ **Choice of Strengths and Thicknesses**
(Multiple wire types to suit various needs and purposes)
- ⦿ **Cost Effective**
(Low cost barbed wire rolls for demarcation or trespass deterrence)
- ⦿ **Galvanised to BS 10346**
(Galvanised finish compliant to latest standards)
- ⦿ **Strength & Resilience**
(High-tensile wire, resistant to stress from movement and animals)


Suitable For

- ⦿ Fields
- ⦿ Crops
- ⦿ Livestock
- ⦿ Demarcation
- ⦿ Deterrence




Deterring

Sharp barbs and unpainted finish gives an intimidating look to help deter trespassers and scavengers.



High-strength wire

High tensile, thin wire gives strength enough to stand against regular pressure from wind, animals and pedestrians.



Size variation

With a variety of wire thicknesses, this barbed wire range is designed to be perfectly fit for purpose.



Corrosion resistant

Galvanised steel with a zinc coating ensures this barbed wire can withstand the elements with minimal upkeep.

Specifications

Roll length	200m
Barb distance	One every 127mm
Barb size	12.7mm point to point
Wire Thicknesses	Mild: 2.50mm/2.00mm High Tensile: 2.00mm/1.89mm Heavy Duty: 1.60mm/1.45mm
Tensile strength	500-600 N/mm2 (Mild, High Tensile) 650-750 N/mm2 (Heavy Duty)
Material	Galvanised mild or high tensile steel (BS 10346)
Finish	Zinc coated for longevity
Roll weight	Mild: 21kg High Tensile: 8.6kg Heavy Duty: 14.6kg
Post Centers	Intermediate strainer post every 3m (approx)

 Call our Expert Sales Team for more information

First Fence Ltd | Kiln Way, Woodville, South Derbyshire, DE11 8EA
01283 512 111 | www.firstfence.co.uk | sales@firstfence.co.uk



Bristol | Canvey | Glasgow | Nottingham | Tipton

