



Key Features

- ✓ **Safety**
(Compliant with BS EN 12453 standards for automatic gate safety)
- ✓ **Bi-Fold Gate**
(No need to plan for swing radius)
- ✓ **Corrosion Resistant**
(Galvanised and PPC to ISO and BS EN standards)
- ✓ **System-Based Solution**
(RapidFold™ gates form a system of elements for access control)

Suitable For

- ✓ Industrial Buildings
- ✓ Airports & Ports
- ✓ Schools & Nurseries
- ✓ Guarded Car Parks
- ✓ Residential



Safety

Automated RapidFold™ gates comply with BS EN 12453 standards for gate safety.




Corrosion Resistant

RapidFold™ gates are hot-dip galvanised and polyester paint coated to secure against corrosion.



Bi-Fold Gate Design

The RapidFold™ gate is a bi-fold gate. The leaf is designed to fold in the middle, allowing for a more efficient use of space. The gate does not contact the floor.



System-Based Solution

These gates form a system of elements for access control. When used together with industrial segments, mesh panels, posts, and gates, they form a complete system.

Specifications

Material	Galvanised steel (ISO 1461)
Infill	Vertical bar or 868 twin mesh
Finish	Polyester powder coated (BS EN 13438)
Colour	A range of RAL colours is available
Post Type	Bolt Down

What's Included:

- Bolt down posts (2x)
- Cat 3 Safety Edges (10x)
- Wireless Safety Edge Transmission System
- Photocells (2 pair)
- Flush Mounted Keyswitch & ES Button
- Flashing light
- Remote Operation Fobs (2x)
- Control Panel (Post Mounted)
- Mechanical Roller Guide System (Electromagnetic Lock on gates over 7m wide)

Optional Extras




AES OPYN-4G GSM Video Intercom



Videx GSM4KCR-1S/4GE-M Intercom



Optex OVS-02GT Above Ground Vehicle Detection Sensor



GNP-1C Car Height Goose Neck Intercom Post

 Call our Expert Sales Team for more information

First Fence Ltd | Kiln Way, Woodville, South Derbyshire, DE11 8EA

01283 512 111 | www.firstfence.co.uk | sales@firstfence.co.uk

Hardware Explained

The RapidFold™ gate system is designed for efficiency and ease. These gate systems come ready to install, with all components supplied with each RapidFold™ gate kit.

Infill Options

These gates have the option of either 868 twin mesh, or a 25mm vertical bar infill, in order to fulfil more needs and purposes.



⌚ Ensures compliance with BS EN 12453

Centre Fold Hinges

All RapidFold™ Gates have a centre hinge to allow the gate leaf to fold, rather than swing, making these gates much more space-efficient.



⌚ Ensures compliance with BS EN 12453

FAAC Nordic - DAAB

The RapidFold™ Pro gate systems use this geared motor intended for heavy usage, ensuring high performance over repeated openings. MT model supplied up to 3.5m widths, MK2 for wider gates.



⌚ Ensures compliance with BS EN 12453

Safety Edges

Avoid damage or injury with these category 3 safety edges, pre-installed for convenience and protection.



⌚ Ensures compliance with BS EN 12453

Bolt Down Posts


These gates come with posts already attached and ready to bolt down using 4 ground anchor bolts per post (supplied separately).



⌚ Ensures compliance with BS EN 12453

Warning Light

Pre-installed safety light flashes orange when gate is moving, to warn anywhere nearby to steer clear of moving parts.



⌚ Ensures compliance with BS EN 12453

Heights & Colours

Gate Height (meters)	6.0	6.25	6.5	6.75	7.0	7.25	7.5	7.75	8.0	8.25	8.5	8.75	9.0	9.25	9.5	9.75	10.0
2.5	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
2.4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
2.3	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
2.2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
2.1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
2.0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	6.0	6.25	6.5	6.75	7.0	7.25	7.5	7.75	8.0	8.25	8.5	8.75	9.0	9.25	9.5	9.75	10.0
	Gate Width (meters)																

Available in standard RAL colours. Custom colours are available on request, as is a galvanised-only option




📞 Call our Expert Sales Team for more information

First Fence Ltd | Kiln Way, Woodville, South Derbyshire, DE11 8EA

01283 512 111 | www.firstfence.co.uk | sales@firstfence.co.uk

Sizing



Sj - clear width

So - distance between posts

Ho - leaf height

L - post height from ground level

W - post dimensions

Gate height Ho	Width between posts	Leaf height from the driveway level	Post dimensions W	Post height L	Required space (without cabinet)	Required space (with DAAB cabinet)
2000	Sj + 300	Ho + 250	200x200	2550	Sj + 900	Sj + 1500
2100	Sj + 300	Ho + 250	200x200	2650	Sj + 900	Sj + 1500
2200	Sj + 300	Ho + 250	200x200	2750	Sj + 900	Sj + 1500
2300	Sj + 300	Ho + 250	200x200	2850	Sj + 900	Sj + 1500
2400	Sj + 300	Ho + 250	200x200	2950	Sj + 900	Sj + 1500
2500	Sj + 300	Ho + 250	200x200	3050	Sj + 900	Sj + 1500



Trade Installer?

Speak to our Sales Team about Trade Pricing on our Specialist Gates & Automation



Call our Expert Sales Team for more information

First Fence Ltd | Kiln Way, Woodville, South Derbyshire, DE11 8EA

01283 512 111

| www.firstfence.co.uk

| sales@firstfence.co.uk