


H2208L  
Bollard

# Semi-Automatic Telescopic with key and LED Ø220 x 500




Metal  
Key

Regulations and certifications:



Bollard designed for controlling the access to the public road, communities of neighbours, companies, etc. AISI-304 satin stainless steel piston, Ø220 x 500 mm height. Top lid, chassis, fixing and screws made of stainless steel. Automatic rising and manual lowering. Automatic locking in both positions, unlocking by means of a DIN3223 triangular key.

		H2208L
DIMENSIONS AND MATERIALS	HEIGHT FROM GROUND LEVEL	500 mm5
	BOLLARD DIAMETER	Ø220mm
	BOX DIMENSIONS	230 x 230x 680 mm
	BOLLARD MATERIAL	Acero inoxidable AISI 304 satinado
FUNCTIONAL FEATURES	SYSTEM	
	WORKING FREQUENCY	400Nw
	ASCENT TIME LOWERING TIME	Mecanismo subida con cilindro gas Mecanismo de bajada - manual
IMPACT RESISTANCE	IMPACT RESISTANCE	80.000 JOULES
	REFLECTIVE BAND	OPCIONAL
	LIGHTED CROWN	SI,LED RGB



Ref.	Ø A	B	C	D	H	H	
H220L8	220	274	340	500	1170	670	8
H220L4	220	274	340	500	1170	670	4

SEMI-AUTOMATIC TELESCOPIC with key Ø220 x 750mm



Downloads: [Project sheet](#) | [CAD](#) | [BIM](#)



V. 2025-07-23 | The constant improvement and evolution of our products may result in some modifications of the technical specifications and characteristics of the products without prior notice.